





SPRINKLER CHART FORM

Reference of the	study														
Dealer															
Customer					File n°										
	New device \square Sprinkler chart only \square Sprinkler chart with supply of equipment \square														
Type of system															
		Full circle p	ivot 🗖			Lat	eral wi	th single s	prinkler chart l	☐ (length	of its cour	se m)			
	Par	t circle pivot \Box	l (angle	°)				Lateral	with double s	orinkler cha	rt 🛘				
Hydraulic input															
	Flow	m3/h					Р	Pressure	bar						
					le pressure at the				Required pr			ie mach	nine 🗆		
		elevation	m compare	ed to pivo	ot point	Ne	egative	elevation	m comp	ared to piv	ot point				
System specifica		T													
Quan		Length			Diameter			Thickness			Outlets per span				
Overh	ang														
		ht under rods	ler rods \rightarrow standard (3.20m) \Box raised (4.00m) \Box hyper raised (4.75m) \Box lowered (i (2.40m) □				
	1101		an 🗖 Fold					te when fo		m3/h					
Sprinkler choice		1 Olding Spa	1010	ing towe	er s position	Desired	IIOW Ia	te when it	nueu III.	1113/11					
Sprinkler enoice				NEL	SON				s	ENNINGER		ко	MET		
		ROTATO			SPINNER	SPRAY	TRAS	HBUSTER	IMPACT	1.34/-b	Xi-Wob	KDT	КРТ		
	Orange	White	Green	Blue	S3000	D3000	Т	Г3000	SENNINGER	I-Wob	Тор	KPT	PEAK		
Up-top															
Galvanized steel drops															
PVC						_									
drops	Ш														
Flexible hose								_							
3m ground clearance															
Flexible hose															
1.5m ground															
clearance															
Pressure choice		No matter ☐ 10 PSI ☐ 15 PSI ☐ 20 PSI ☐ 30 PSI ☐ 40 PSI ☐ 50							PSI 🗖 50 PS	SI 🔲 Nor	ne 🗖				
			Ton of nine (hefore th	ne gooseneck)	I Top of ni	ine laft	er the god	seneck hefor	the nine)	П				
Regulators position	Top of pipe (before the gooseneck) \square Top of pipe (after the gooseneck, before the pipe) \square Bottom of pipe (after the drop, before the sprinkler) \square														
Options		Standard mounting Drops on rods Dual drops Dry wheels system D													
Options	Standard mountains — Drops on rous — Duardrops — Dry wheels system —														
Special request															
End gun															
End Spray		End Spray	R55		P85	SR	SR75		SR100	SKIPPER		Twin Max			
No booster pump							<u> </u>								
						□3hp			np 🗖 4hp	□3hp □ 4hp					
Booster pump							□ 5hp		☐ 5hp	□ 5hp		□ 5hp			
If 2 endgun			1		Г	☐ Both on				Toogle		— 5/1/p			
_		☐ circular	rcular 🔲 circular			□ circular □ circular				□ circular		☐ circular			
		□ linear				□ linear		□ linear		□ linear		□ linear			
								eir attribution (lateral and/or circular r							
Drive chain		·	·												
Motor			Gearbox			Wheels				Frequency					
Comments															

120 Chemin de la Sablière 64270, Puyoô - France • Tél: +33 5 59 65 12 19 • Fax: +33 5 59 65 20 05 • otech-sa@otech.fr • www.otech.fr OTECH S.A.S. au capital de 1 920 000 € • 390 530 061 R.C.S. PAU • FR 42 390 530 061 • CODE APE 2830Z

